

| IDENTIFICATION | | | Released | Issue No. |
|----------------|-----------------|---------------------------|------------|-----------|
| | MSB-5-20354-005 | Liquid Spray Wrap Remover | 22/11/2013 | RA07 |

| COMPOSITION/INFORMATION ON INGREDIENT | (*) Denotes - See OTHER INFORMATION | VOC | I.000 |
|---------------------------------------|-------------------------------------|-----|-------|
|---------------------------------------|-------------------------------------|-----|-------|

| INGREDIENT NAME | CONC % | TWA (8hr) PPM | TWA (15mins) PPM | R PHRASES |
|---------------------------|---------|---------------|------------------|-----------|
| ALIPHATIC PETROLEUM ETHER | 90-100% | 125 | * | F11 |
| ISO PROPANOL | 0-5% | 400 | 500 | F11 |

| HAZARD IDENTIFICATION | HIGHLY FLAMMABLE. EXPLOSIVE VAPOUR. LIQUID IRRITATING TO SKIN, EYES AND RESPIRATORY SYSTEM. |
|-----------------------|---|
|-----------------------|---|

FIRST AID MEASURES

| | |
|-------------|---|
| EYES: | WASH WITH WATER. |
| SKIN: | WASH WITH SOAP & WATER. LAUNDER SOAKED CLOTHING BEFORE RE-USE. |
| INHALATION: | REMOVE TO FRESH AIR. GET MEDICAL AID IF UNCONSCIOUS TURN TO RECOVERY POSITION. |
| INGESTION: | DO NOT INDUCE VOMITING. GET MEDICAL AID. IF PATIENT VOMITS TURN TO RECOVERY POSITION. |

| FIRE FIGHTING MEASURES | USE CARBON DIOXIDE, DRY CHEMICAL, SAND OR EARTH. USE WATER FOG TO COOL SURFACES. |
|------------------------|--|
|------------------------|--|

| ACCIDENTAL RELEASE MEASURES | ELIMINATE SOURCES OF IGNITION. AVOID INHALING VAPOUR. EVACUATE PERSONNEL. ABSORB LIQUID WITH NON COMBUSTIBLE MATERIAL. IF PRODUCT HAS ENTERED DRAINS INFORM FIRE BRIGADE. |
|-----------------------------|---|
|-----------------------------|---|

HANDLING AND STORAGE

| | |
|----------------------|---|
| USAGE PRECAUTIONS: | USE IN A FLAME PROOF AREA. FURTHER INSTRUCTIONS ON CONTAINER OR DATA SHEET. |
| STORAGE PRECAUTIONS: | KEEP CONTAINER CLOSED. STORE IN A COOL DRY WELL VENTILATED AREA AWAY FROM SOURCES OF IGNITION.NO SMOKING. |

PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|-------------------|--------------------------------|--------------------|----|
| APPEARANCE: | LOW VISCOSITY CLEAR LIQUID GEL | | |
| FLASHPOINT (C): | -30 | BOILING POINT (C): | 63 |
| EVAPORATION RATE: | | EXPLOSIVE LIMIT: | |
| SPECIFIC GRAVITY: | 0.70 | SOLUBILITY @ 20 C: | |

EXPOSURE CONTROLS AND PERSONAL PROTECTION

| | |
|--------------|---|
| RESPIRATORY: | AVOID INHALING VAPOUR USE WITH CONTROLLED EXTRACTION AND/OR APPROVED FACE MASK. |
| SKIN: | USE IMPERVIOUS GLOVES & OVERALLS. |
| EYES: | IF THERE IS RISK TO EYES USE APPROVED SAFETY GLASSES OR GOGGLES. |

STABILITY AND REACTIVITY

| |
|---|
| STABLE UNDER NORMAL STORAGE CONDITIONS. |
|---|

TOXICOLOGICAL INFORMATION

| | |
|--------------------|--|
| SKIN TOXICITY: | CHRONIC SKIN CONTACT MAY CAUSE DERMATITIS. |
| EYE TOXICITY: | IRRITATING TO EYES. |
| INHALED TOXICITY: | MAY CAUSE DROWSINESS, NAUSEA, DIZZINESS. |
| INGESTED TOXICITY: | MAY CAUSE VOMITING, IRRITATION OF DIGESTIVE TRACT. |

ECOLOGICAL INFORMATION

| |
|--|
| UNLIKELY TO BIOACCUMULATE. LOW TOXICITY TO FISH. |
|--|



DISPOSAL CONSIDERATIONS

| |
|--|
| LAND FILL OR INCINERATE IN ACCORDANCE WITH LOCAL REGULATIONS USING AUTHORISED PERSONNEL. |
|--|

TRANSPORT INFORMATION

| | | | |
|----------------|------|-----------------------|-------|
| UN NUMBER: | 1263 | PROPER SHIPPING NAME: | PAINT |
| IMDG CLASS: | 3 | MARINE POLLUTANT: | NO |
| PACKING GROUP: | II | ADR/RID: | 3 |

REGULATORY INFORMATION

| | | |
|-----------------|---|--------------------------------|
| LABEL SYMBOLS: |   | EXTREMELY FLAMMABLE. IRRITANT. |
| RISK PHRASES: | R11 HIGHLY FLAMMBLE.UN 1263 PAINT RELATED PRODUCT | |
| SAFETY PHRASES: | S 7/9 S16 KEEP AWAY FROM SOURCES OF IGNITION.NO SMOKING. S24/25 AVOID CONTACT WITH SKIN AND EYES.S33. TAKE PRECAUTIONS AGAINST STATIC DISCHARGE | |

OTHER INFORMATION

Every effort has been made to keep the information contained on this document as accurate as possible. However the company cannot be held responsible for any errors contained within

* Application Instructions

- Using a brush, carefully apply the Liquid Wrap Remover over the Liquid Wrap Pro or High Build Primer.
- Immediately remove any excess Remover that may have overlapped onto OEM paint with a rag directly after application.
- Leave for 10-15 minutes until the Liquid Wrap Pro or High Build Primer starts to soften and then peel.
- Depending on age and thickness of the Liquid Wrap Pro or High Build Primer, repeating the process may be necessary.
- After the wrap has been removed wash the entire area (including nearby OEM paint) with warm, soapy water.